



# Silkolene®



## Race Technical Data

### BOA 90 LS

## High Performance Gear And Limited Slip Differential Oil

#### Description

BOA 90 LS is a high performance mineral based gear oil for hypoid and spiral bevel axles, which has excellent extreme pressure, anti-corrosion, anti-oxidation and anti-foam properties.

#### Advantages / Benefits

- Excellent load carrying properties.
- Contains friction modifiers.

#### Application

This unique formula contains friction modifiers designed to make BOA 90 LS ideal for limited slip differentials operating under severe conditions including competition use.

#### Specifications

- Very high levels of the latest load carrying and anti-wear agents give API GL5 and GL6 performance.

January 2006 GDUK Page 1 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.



# Silkolene®



## Race Technical Data

### Typical Data: BOA 90 LS

Characteristics	Unit		Test Method
Kinematic Viscosity at 100°C	mm <sup>2</sup> /s	19.8	IP71
at 40°C	mm <sup>2</sup> /s	230	
Viscosity Index (VI)		99	IP226
Specific Gravity @ 15°C		0.898	IP160
Flash Point (Closed Cup)	°C	205	IP34

January 2006 GDUK Page 2 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.

FUCHS LUBRICANTS (UK) PLC.  
New Century Street, Hanley  
GB-Stoke-on-Trent, Staffordshire, ST1 5HU

Tel: +44-8701 -20 04 00  
Fax: +44-1782 -20 20 73  
contact-uk@fuchs-oil.com  
<http://www.fuchslubricants.com>