

Product INFORMATION

FUCHS (UK) PLC.
New Century Street
Hanley
GB-Stoke-on-Trent,
Staffordshire, ST1 5HU



TITAN SUPERSYN 5W-40

High Performance, Fully Synthetic, Engine Oil

Description

High performance, year round, SAE 5W/40 fuel economy engine oil.

Application

For normally aspirated and turbocharged car and van petrol and diesel engines.

Miscible with all mineral oil and synthetic based engine oils. No flushing is therefore necessary.

Specifications

- ACEA A3, B3, B4
- API SM/CF
- BMW Special Approval
- Porsche Special Approval
- VW 505 00 and 502 00
- Mercedes-Benz 229.3
- Registered with MG Rover

Advantages / Benefits

- Reduces exhaust particulate emissions because of the extremely low evaporation losses of synthetic oils at high temperatures
- Ensures immediate protection on engine start-up
- Outstanding engine protection under all conditions ensures maximum life of all engine components
- Optimum function of hydraulic tappets due to rapid oil circulation and the absence of foaming
- Low viscosity gives potential for fuel economy



October 2006 GDUK Page 1 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.

Product INFORMATION

FUCHS (UK) PLC.
New Century Street
Hanley
GB-Stoke-on-Trent,
Staffordshire, ST1 5HU



Typical Data: TITAN SUPERSYN 5W-40

Characteristics	Unit		Test Method
SAE Grade		5W/40	DIN 51 511
Kinematic viscosity at 100°C	mm ² /s	13.6	IP71
at 40°C	mm ² /s	82.4	
Viscosity at -25°C	mPas	3340	ASTM D 2602
Viscosity index		162	ASTM D 2270
Flash point (PMCC)	°C	231	IP34
Specific gravity 15°C	g/ml	0.850	ASTM D 1298
Pour point	°C	-39	IP15

October 2006 GDUK Page 2 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.