



## Mobil Extra 4T

### Superior Performance Four-Stroke Motorcycle Engine Oil

#### Product Description

Mobil Extra 4T is a high performance, semi-synthetic blend technology four-stroke motorcycle engine oil developed to provide boosted engine cleanliness and protection for all types of motorcycles and operation.

#### Features and Benefits

Mobil Extra 4T combines a unique blend of high quality mineral and synthesised hydrocarbon baseoils together with an advanced additive system to provide excellent engine cleanliness, wear protection and effective corrosion. Key features and benefits include:

Features	Advantages and Potential Benefits
Excellent wear protection	Longer engine component and overall engine life
Good thermal , oxidation stability and deposit control	Cleaner running engines resulting in smooth flawless operation
Excellent corrosion protection properties	Longer life of valve train and bearing components
Enhanced low temperature properties	Easier cold weather starting, longer electrical system life

#### Applications

Mobil Extra 4T is specifically recommended for lubrication of all types of four-stroke motorcycle engines, where the latest industry standard qualities are required.

#### Specifications and Approvals

**Mobil Extra 4T meets or exceeds the requirements of the following industry specifications:**

API SL

JASO MA

#### Typical Properties

Mobil Extra 4T	
SAE	10W-40
Viscosity, ASTM D 445	
cSt @ 40° C	98
cSt @ 100° C	14.4
Viscosity Index, ASTM D 2270	157
Sulfated Ash, wt%, ASTM D 874	0.9
Pour Point, °C, ASTM D 97	-30
Flash Point, °C, ASTM D 92	A
Density @15° C kg/l, ASTM D 4052	A

#### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended

application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

The Mobil logotype, the Pegasus design and Extra 4T are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.

9-2010

Esso Petroleum Company limited  
ExxonMobil House, Ermyn Way, Leatherhead, Surrey KT22 8UX

44 (0)1372 222000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

© 2001-2010 Exxon Mobil Corporation. All rights reserved.