



# Silkolene®

Maintain Technical Data



## PRO COOL

# Advanced All Season Reduced Toxicity Engine Coolant

### Description

The product is based on propylene glycol and hence gives a very safe level of toxicity when compared to ethylene glycol based anti-freezes. The PRO COOL formulation includes 50% distilled water to give zero lime scale deposits, optimum frost protection in severe winter conditions, plus excellent anti-corrosion performance.

The balanced inhibitor system incorporated in FUCHS SILKOLENE PRO COOL is the result of several years research and development and is designed to protect the cooling system against foaming, scale formation and corrosion. Anti-cavitation performance exceeds that of conventional ethylene glycol based anti-freezes, providing the user with superior protection against engine and coolant pump damage due to this phenomenon.

### Application

FUCHS SILKOLENE PRO COOL is a **ready-to-use** high performance automotive antifreeze and engine coolant for all year round use.

Do **not** dilute FUCHS SILKOLENE PRO COOL with water, this will reduce its anti-corrosion performance and frost protection level.

### Advantages / Benefits

- PRO COOL is compatible with all alloys, plastics, elastomers and gasket materials used in modern engine cooling systems.
- Ready-to-use - no dilution required.

January 2006 GDUK Page 1 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.



# Silkolene®



## Maintain Technical Data

### Typical Data: PRO COOL

Characteristics	Unit		Test Method
Appearance		Clear Blue Liquid	
Specific Gravity at 20°C		1.048	IP160
Refractive Index at 15°C		1.391	
Freezing Protection	°C	-32	

January 2006 GDUK Page 2 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.

FUCHS LUBRICANTS (UK) PLC.  
New Century Street, Hanley  
GB-Stoke-on-Trent, Staffordshire, ST1 5HU

Tel: +44-8701 -20 04 00  
Fax: +44-1782 -20 20 73  
contact-uk@fuchs-oil.com  
<http://www.fuchslubricants.com>