



Silkolene®



Scoot Technical Data

SCOOTER GEAR OIL 80W-90

Advanced Transmission Oil

Description

Packed in an easy-to-use one-shot 125ml tube, SCOOTER GEAR OIL 80W-90 is ideal for use in all scooters where an SAE 85W-90 or 80W-90 lubricant is specified.

Application

FUCHS SILKOLENE SCOOTER GEAR OIL 80W-90 has been formulated specifically for use in scooters and mopeds.

Specifications

- API Gear Rating GL4

Advantages / Benefits

- Minimises wear and protects oil seals.
- Reduces friction losses.
- Gives outstanding lubrication performance and efficient power transmission, ensuring total reliability and minimal transmission noise.

January 2006 GDUK Page 1 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.



Silkolene®



Scoot Technical Data

Typical Data: SCOOTER GEAR OIL 80W-90

Characteristics	Unit		Test Method
Kinematic Viscosity at 100°C	mm ² /s	15.0	IP71
at 40°C	mm ² /s	151.2	
Viscosity Index (VI)		99	IP226
Pour point	°C	-28	IP15
SAE Rating - Gearbox		80W-90	
SAE Rating - Engine		20W-50	

January 2006 GDUK Page 2 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.