

Product

INFORMATION

FUCHS (UK) PLC.
New Century Street
Hanley
GB-Stoke-on-Trent,
Staffordshire, ST1 5HU



SILKOLENE SILKOLUBE SAE 20W/50

For The Cherished Older Car

Description

SILKOLENE SILKOLUBE SAE 20W/50 is a multigrade motor oil developed for economical protection of many petrol engines in passenger cars and light commercial vehicles operating under normal service conditions over a wide range of temperatures.

It is particularly suitable for use in older cars.

Specifications

SILKOLENE SILKOLUBE SAE 20W/50 is designed to meet or exceed the following requirements:

- API SF/CC

Advantages / Benefits

- Good detergent/dispersant performance to ensure engine cleanliness.
- Good anti-wear, anti-oxidation and anti-rust properties.
- Viscosity and performance level suited to older engines.



June 2002 GDUK Page 1 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.

Product INFORMATION

FUCHS (UK) PLC.
New Century Street
Hanley
GB-Stoke-on-Trent,
Staffordshire, ST1 5HU



Typical Data: SILKOLENE SILKOLUBE SAE 20W/50

Characteristics	Unit		Test Method
Kinematic viscosity @ 100°C	mm ² /s	18.4	IP71
@ 40°C	mm ² /s	146.0	
Viscosity index		141	IP226
Flash point (PMCC)	°C	190	IP34
Pour point	°C	-25	IP15

June 2002 GDUK Page 2 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.