



Silkolene®

Ride Technical Data



SUPER 2 PREMIX SAE 30

MC-Syn Technology - Molecularly Converted Semi-Synthetic Universal Premix 2-Stroke Engine Oil

Description

FUCHS SILKOLENE SUPER 2 PREMIX SAE 30 gives piston cleanliness, high thermal stability, anti-wear and corrosion protection. Minimises port fouling, ring sticking and spark plug whiskering.

Application

SUPER 2 PREMIX SAE 30 is a specially formulated lubricant for 2-stroke petrol engines. Recommended for most 2-stroke motorcycles as well as chain saws and lawn mowers.

Always mix to the manufacturer's recommendation.

Specifications

- API 2-Cycle Performance Spec. TC
- JASO FB

Advantages / Benefits

- Low ash gives superior spark plug and combustion chamber cleanliness.
- Does not contain a spirit diluent (e.g. Kerosene) ensuring safe storage in high ambient temperatures and retention of lubricant film strength.
- Excellent anti-wear and anti-corrosion features protect against ring sticking and piston seizure thus giving long engine life and reliability.
- Formulation gives good storage protection for seasonally used engines.

January 2006 GDUK Page 1 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.



Silkolene®



Ride Technical Data

Typical Data: SUPER 2 PREMIX SAE 30

Characteristics	Unit		Test Method
Kinematic Viscosity at 100°C	mm ² /s	11.84	IP71
at 40°C	mm ² /s	105.6	
Viscosity Index (VI)		100	IP226
SAE Rating		30	
Flash Point (Closed Cup)	°C	220	IP34
Specific Gravity @ 15°C		0.879	IP160
Calcium Content	% wt.	0.013	
Appearance		Red	

January 2006 GDUK Page 2 of 2

The above information is supplied to the best of our knowledge and belief on the basis of the current state-of-the-art and our own development work. Subject to amendment.