



EDGE Turbo Diesel 0W-30

For Modern High Performance Diesel Engines

Applications

Castrol EDGE Turbo Diesel 0W-30 is a product designed to work with Diesel Engines to clean exhaust systems and reduce emissions.

This product meets the latest requirements of BMW petrol and diesel engines and is approved to meet latest BMW LL04 specs.

Castrol EDGE Turbo Diesel works with engines fitted with particle filters and prevent blocking. Plus this product is based on new low SAPS technology (Suphated Ash, Phosphorus and Sulphur).

Features / Benefits

Provides modern diesel car engines with Castrol's best protection technology from start-up.

Keeps engines running cooler.

Maximises power by keeping exhaust filters flowing freely.

Synthetic technology.

Specifications / Performance

API SM/CF
ACEA A3/B3/B4/C3

BMW Longlife-04
MB 229.31

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

EDGE Turbo Diesel 0W-30

For Modern High Performance Diesel Engines

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

	Test Methods	Units	Value:
SAE 0W-30			

Test	Method(s)	Unit	Typical
Density at 15°C	ASTM D4052		0.8383
Appearance	Visual		Bright and clear
Viscosity 100°C	ASTM D445	mm ² /s	12.3
Viscosity 40°C	ASTM D445	mm ² /s	71
Viscosity Index	ASTM D2270	None	170
CCS -35°C	ASTM D5293	cP	5900
Flash Point, PMCC	ASTM D93	°C	238
Ash, Sulphated	ASTM D874	% wt	0.64
Total Base Number, TBN	ASTM D2896	mg KOH/g	6.69
Pour Point	ASTM D97	°C	-57

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol (UK) Ltd
Wakefield House
Pipers Way
Swindon
Wiltshire
SN3 1RE

Lubricants Helpline: 01793 452222
Orders/Enquiries: 08459 123011