



GTX

strong all-round mineral performance

Applications

Castrol GTX 10W-40 is a mineral engine oil and this viscosity of engine oil is widely recommended for a variety of engines manufactured since 1990.

Features / Benefits

Many standard oils on the market have failed to keep pace with the latest technological developments, but with Castrol GTX for Modern engines you can be sure of buying "Liquid Engineering" for your car.

Specifications / Performance

ACEA A3/B3
API SL/CF

MB 229.1
VW 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

GTX

strong all-round mineral performance

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

	Test Methods	Units	Value:
--	--------------	-------	--------

SAE 10W-40

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Typical</i>
Density @ 15C, Relative	ASTM D4052		0.875
Appearance	Visual		Clear & Bright Amber Liquid
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	100
Viscosity Index	ASTM D2270		149
Viscosity, CCS -25C (10W)	ASTM D5293	cP	7000 max
Flash Point, PMCC	ASTM D93	°C	194
Ash, Sulphated	ASTM D874	% wt	1.05
Total Base Number, TBN	ASTM D2896	mg KOH/g	8

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol (UK) Ltd
Wakefield House
Pipers Way
Swindon
Wiltshire
SN3 1RE

Lubricants Helpline: 01793 452222
Orders/Enquiries: 08459 123011