



GTX High Mileage

For engines over 75,000 miles

Applications

New Castrol GTX High Mileage is an SAE 15W-40, mineral engine oil which has been specifically formulated for engines which have covered over 75,000 miles. Its special combination of additives helps prolong your engine life.

Castrol GTX High Mileage is recommended primarily for petrol engines.

Castrol GTX High Mileage contains specially developed seal conditioners to preserve the elasticity of the engine seals

Features / Benefits

Unique anti-wear formulation guards against engine wear, helping prolong the engine life

Seal elasticity aids in the control of oil leaks in the engine, because damaged seals can cause the engine to burn more oil.

A reduction in oil loss through burning, further lessens exhaust emissions, which helps the environment.

Specifications / Performance

ACEA A3/B3
API SL/CF
MB 229.1
VW 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

Test Methods	Units	Value:
--------------	-------	--------

SAE 15W-40

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Typical</i>
Density @ 15C, Relative	ASTM D4052		0.885
Appearance	Visual		Clear & bright amber liquid
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	14.03
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	107
Viscosity Index	ASTM D2270		131

Viscosity, CCS -20C (15W)	ASTM D5293	cP	
Flash Point, PMCC	ASTM D93	°C	196
Ash, Sulphated	ASTM D874	% wt	1
Total Base Number, TBN	ASTM D2896	mg KOH/g	8

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol (UK) Ltd
Wakefield House Lubricants Helpline: 01793 452222
Pipers Way Orders/Enquiries: 08459 123011
Swindon
Wiltshire
SN3 1RE

Date Created: 16/01/2006 18:34:29 Last Modified: 16/01/2006
