



Act>Evo 2T

Applications

Castrol Act>Evo 2T is a modern, high quality 2-stroke engine oil for modern engines. Its Deposit Protection Formula is designed to provide continuous protection against the build up of carbon deposits on the engine and spark plug during use, keeping them clean to ensure fast and reliable starting.

Castro Act>Evo 2T is suitable for use in all 2-stroke motorcycle and scooter engines from both European and Japanese Manufacturers. It is designed for both oil injection and pre-mix lubrication, as per manufacturers' instructions, up to a fuel to oil ratio of 50:1.

Features / Benefits

- High performance additives protect components from deposits in use
- Good lubricity, protecting pistons from scuffing
 - Good protection against exhaust system blocking
 - Low ash formulation to reduce pre-ignition & catalyst deterioration
 - Designed for both oil injection and pre-mix systems up to 50:1
-

Specifications / Performance

Exceeds JASO FC and API TC

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

Test Methods

Units

Value:

SAE N/A

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Min</i>	<i>Typical</i>	<i>Max</i>
Density @ 15C, Relative	ASTM D4052	g/ml		0.8634	
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	6.5	6.9	8.0
Viscosity, Kinematic 40C	ASTM D445	mm ² /s	37.0	37.4	38.5
Flash Point, PMCC	ASTM D93	°C	70	73	
Pour Point	ASTM D97	°C		-45	-39
Colour	ASTM D1500			1.5	

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE www.castrol.com/uk
 Telephone: 01793 512712
 Automotive Technical Helpline: 01793 452222
 Orders/Enquiries: 0845 6008125 (Workshop Customer Order Line) 0845 6008131 (Retail Customer Order Line)

Castrol Ireland, Suit 12, Plaza 212, Blanchardstown Business Park Phase 2, Blanchardstown, DUBLIN 15, Ireland www.castrol.com/ie
 Automotive Technical Helpline: 1800 509 353
 Orders/Enquiries: 01 866 5100
