



Act>Evo GP 4T

Applications

Castrol Act>evo GP 4T is modern, high quality 4-stroke engine oil designed with a special Wear Protection Formula to give both reliable engine starting and continuous trouble free running throughout the oil drain period.

Castrol Act>evo GP's Wear Protection Formula, combined with Trizone Technology™ helps to continually maintain the protecting and lubricating properties of the oil by reducing wear, controlling excessive oil thickening, and keeping critical components clean. This helps to maintain the health of your engine, leading to reliable starting and trouble free running.

Castrol Act>evo GP 4T is suitable for all modern motorcycle engines where API and or JASO specifications are recommended.

Features / Benefits

- Special Wear Protection additives for continuous "start and go" protection.
- Outstanding oxidation and wear control throughout the drain period.
 - Trizone Technology™ for protection of the engine, clutch and gears.
 - Complies with requirements of catalyst equipped engines
-

Specifications / Performance

SAE 20W50, API SG, JASO MA-2

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

Test Methods

Units

Value:

SAE 20W-50

<i>Test</i>	<i>Method(s)</i>	<i>Unit</i>	<i>Min</i>	<i>Typical</i>	<i>Max</i>
Density @ 15C, Relative	ASTM D4052	g/ml		0.888	
Appearance	Visual			C&B	
Viscosity, Kinematic 100C	ASTM D445	mm ² /s	18.5	19.0	19.5
Viscosity, Kinematic 40C	ASTM D445	mm ² /s		180	
Viscosity Index	ASTM D2270	None		120	
Viscosity, CCS -15C (20W)	ASTM D5293	cP		9000	9500
Flash Point, PMCC	ASTM D93	°C	180	210	
Total Base Number, TBN	ASTM D2896	mg KOH/g		8.1	
Pour Point	ASTM D97	°C		-24	-18

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication. It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE www.castrol.com/uk
 Telephone: 01793 512712
 Automotive Technical Helpline: 01793 452222
 Orders/Enquiries: 0845 6008125 (Workshop Customer Order Line) 0845 6008131 (Retail Customer Order Line)

Castrol Ireland, Suit 12, Plaza 212, Blanchardstown Business Park Phase 2, Blanchardstown, DUBLIN 15, Ireland www.castrol.com/ie
 Automotive Technical Helpline: 1800 509 353
 Orders/Enquiries: 01 866 5100
