



Motorcycle DWF

Applications

Castrol Motorcycle DWF is a multi purpose aerosol penetrant and de-watering fluid for motorcycles. It provides excellent displacement of moisture from engine ignitions and electrical contacts. It protects against corrosion and frees corroded parts.

Castrol Motorcycle DWF is suitable for all makes of on and off road motorcycle and scooter.

CAUTION: THIS PRODUCT IS FLAMMABLE. REFER TO LABEL FOR HEALTH AND SAFETY INSTRUCTIONS

Features / Benefits

Castrol Motorcycle DWF provides high standards of:-

- l displacement of moisture
 - l penetration of clean and corroded parts
 - l protection of all metal surfaces against rust
 - l water repellent properties
 - l lubrication of inaccessible mechanisms
-

Specifications / Performance

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical Characteristics

Test Methods

Units

Value:

SAE

Test	Data
Total Solids %	30
Relative Density @15.6°C	0.818
Flash point, (closed) °C	40 typical
Film thickness	4.2 microns (0.16 thou)

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol UK Ltd, Wakefield House, Pipers Way, SWINDON, Wiltshire. SN3 1RE www.castrol.com/uk
Telephone: 01793 512712
Automotive Technical Helpline: 01793 452222
Orders/Enquiries: 0845 6008125 (Workshop Customer Order Line) 0845 6008131 (Retail Customer Order Line)

Castrol Ireland, Suit 12, Plaza 212, Blanchardstown Business Park Phase 2, Blanchardstown, DUBLIN 15, Ireland www.castrol.com/ie
Automotive Technical Helpline: 1800 509 353
Orders/Enquiries: 01 866 5100
