



millersoils.co.uk

PRODUCT DATA SHEET

Motorsport



AUTOMOTIVE



DATA SHEET NO: 6163

PRODUCT NAME/VISCOSITIES:

CRX 75w140 NT

DESCRIPTION:

Competition heavy-duty synthetic transmission oil for highly stressed applications. A blend of synthetic base stocks and shear stable viscosity modifiers. Incorporates "Nano Technology" additive chemistry to significantly reduce internal frictional and power losses, combined with extreme pressure additives.

APPLICATION:

Use as received for competition transmission systems which are subject to high stresses or arduous applications e.g. long distance racing on very high power and torque output. Recommended where full synthetic oil is specified, including synchromesh and 'dog' gearboxes.

USER BENEFITS:

- Exceptional cold flow properties for easier gear changes.
- Very good oxidation resistance and superior thermal stability.
- Low friction formulation to help reduce operating temperatures.
- High film strength for maximum component protection.
- Reduces friction and wear.
- Significantly reduces friction, temperature, wear and minimises power loss.
- Proven solution to gearbox problems in high performance rally cars.

PERFORMANCE PROFILE:

- | | | | |
|--------------------|--------------|--------------|--------------|
| • API GL4
2105E | API GL5 | API MT-1 | MIL-PRF- |
| • ZF TE-ML-05B | ZF TE-ML-07A | ZF TE-ML-12B | ZF-TE-ML-16F |
| • ZF TE-ML-17B | | | |

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	75w140
Specific Gravity @ 15°C	0.874
Kinematic Viscosity @ 100°C	>24.0cSt
Brookfield Viscosity @ -40°C	149,000mPas

HEALTH AND SAFETY:

Health and Safety Data Sheet 6163 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

