



millersoils.co.uk

PRODUCT DATA SHEET

Motorsport



DATA SHEET NO: 6155

PRODUCT NAME/VISCOSITIES:

CRX 75w90 NT

DESCRIPTION:

Competition full synthetic transmission oil. A blend of full synthetic base oils incorporating new "Nano Technology" additive chemistry to significantly reduce internal frictional and power losses.

APPLICATION:

Use as received for the lubrication of competition gearboxes, and axles, which require API GL4 or GL5 performance.

Suitable for use in synchromesh and sequential gearboxes. Ideal for combined synchromesh gearbox and limited slip differentials.

Recommended for modern transmissions where full synthetic oil is specified, especially for high performance road and track day applications.

USER BENEFITS:

- Exceptional cold flow properties for easier gear changes.
- Fast lubrication flow to component extremes on start up.
- Very good oxidation resistance and superior thermal stability.
- Low friction/low drag formulation to help reduce operating temperatures.
- High film strength for maximum component protection.
- Significantly reduces friction, temperature, wear and minimises power loss.

PERFORMANCE PROFILE:

- | | | | |
|----------------|--------------|--------------|---------------|
| • API GL4 | API GL5 | API MT-1 | MIL-PRF-2105E |
| • ZF TE-ML-02B | ZF TE-ML-05B | ZF TE-ML-07A | ZF TE-ML-12B |
| • ZF TE-ML-16F | ZF TE-ML-17B | ZF TE-ML-19C | ZF TE-ML-21B |

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	75w90
Specific Gravity @ 15°C	0.897
Kinematic Viscosity @ 100°C	17.3cSt
Brookfield Viscosity @ -40°C	88,000mPas

HEALTH AND SAFETY:

Health and Safety Data Sheet 6155 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

