



millersoils.co.uk

PRODUCT DATA SHEET

Motorsport



AUTOMOTIVE



DATA SHEET NO: 5792

PRODUCT NAME/VISCOSITIES:

CVL TURBO

DESCRIPTION:

Octane booster and combustion enhancer based on advanced manganese chemistry.

APPLICATION:

Use as received, 1 bottle [500 mls] to 20 litres [maximum] unleaded petrol for all motorsport applications.

Precise treatment levels should be determined by test bed experimentation.

USER BENEFITS:

- Use with modern fuels to increase octane levels by up to 4 octane numbers (40 points).
- Provides improved performance for race, rally or track day.
- Provides similar flame front control as lead, thereby enabling engines to run more advanced ignition timing without danger of pre-ignition or detonation.
- Mixes with leaded, unleaded, LRP and other fuels containing octane enhancing additives such as oxygenates, ethanol and MTBE.
- Equally effective in modern engines fitted with knock sensors and catalytic convertors.

PERFORMANCE PROFILE:

- For maximum benefit use in conjunction with premium, higher octane unleaded fuel.
- Used by an increasing number of engine builders to compensate for the deterioration in pump fuel.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.910
Flashpoint °C	25

Colour Pale Orange Liquid Avoid Light and Heat

HEALTH AND SAFETY:

Health and Safety Data Sheet 5792 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

