



millersoils.co.uk

PRODUCT DATA SHEET
PREMIUM



DATA SHEET NO: 6043

PRODUCT NAME/VISCOSITIES:

MILLERMATIC ATF + 4

DESCRIPTION:

Premium Automatic Transmission Fluid technology blended into selected synthetic base fluids.

APPLICATION:

Use as received in automatic transmissions and other equipment, which require this type of lubricant i.e. Chrysler, Dodge, Plymouth, Jeep and Eagle, and supersedes ATF + 3 standard.

USER BENEFITS:

- Backwards compatible with ATF + 3 fluids.
- Superior wear protection and anti shudder durability.
- Improved low temperature flow.
- Extended transmission life.
- Reduced maintenance costs.
- Improved gearshift performance.

Millermatic ATF + 4 provides:-

- Excellent high temperature oxidation stability up to 100,000 miles under normal conditions
- Stable friction properties which increases durability to meet longer warranty periods
- Outstanding low temperature fluidity providing exceptional cold flow properties.

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.847
Kinematic Viscosity @ 100°C	7.51cSt
Kinematic Viscosity @ 40°C	33.2cSt
Viscosity Index	204
Pour Point °C	-51
Flashpoint °C	198
Brookfield Viscosity @ -40°C	8,380cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 6043 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

