



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



DATA SHEET NO: 5548

PRODUCT NAME/VISCOSITIES:

MILLERMATIC ATF DM

DESCRIPTION:

Premium Automatic Transmission Fluid technology blended into selected synthetic base fluids.

APPLICATION:

Use as received in automatic transmissions and other equipment, which require this type of lubricant.

USER BENEFITS:

- Easier shifting even at low temperatures.
- Shorter warm up ensures max gearbox efficiency.
- Stays in grade even under extreme conditions.
- Lower maintenance costs.
- Longer drain periods.

Millermatic ATF DM provides:-

- Excellent high temperature oxidation stability up to 100,000 miles under normal conditions
- Stable friction properties increases durability, to meet longer warranty periods.
- Outstanding low temperature fluidity which provides exceptional cold flow properties.

PERFORMANCE PROFILE:

- General Motors Dexron IIIH
- Ford Mercon
- MB 236.1 & 236.5
- Voith 55.6335
- Volvo 97341
- Caterpillar TO-2
- Allison C4, V730 & TES 389
- ZF TEML 14A, 09B
- MAN 339 Type F, Z1, VC1
- Vickers, Hagglunds Denison, Racine, Rexnord, Sundstrand and Clark Powershift,

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.865
Kinematic Viscosity @ 100°C	7.41cSt
Viscosity Index	210
Pour Point °C	-51
Flashpoint °C	185
Brookfield Viscosity @ -40°C	12,060cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 5548 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
 Limited
 Brighouse
 West Yorkshire
 WF6 2BB

Tel +44 (0)1484 713201
 Fax +44 (0)1484 721263
 Email enquiries@millersoils.co.uk
www.millersoils.co.uk

