



millersoils.co.uk

PRODUCT DATA SHEET

**PREMIUM**



DATA SHEET NO: 6213

**PRODUCT NAME/VISCOSITIES:**

**MILLERMATIC ATF SPIII**

**DESCRIPTION:**

An automatic transmission and power steering fluid.

**APPLICATION:**

For use in automatic transmission and power steering systems as recommended by the vehicle manufacturer.

**USER BENEFITS:**

- Formulated to meet the latest Japanese and Korean vehicle manufacturer requirements.
- Very high resistance to oxidation and degradation in use and so suitable for use where very long service intervals are required.
- Ensures a smooth transmission of power.

**PERFORMANCE PROFILE:**

Suitable for use where the following specifications are called for by the vehicle manufacturer:-

- Mitsubishi SP – II and SP – III
- Toyota T-III, T- IV and Toyota WS
- Nissan Matic – D and Matic - J
- Hyundai and Kia rebrands of Mitsubishi fluid
- Subaru Special ATF
- JASO M315 1A
- GM Dexron III
- Ford Mercon

**TYPICAL CHARACTERISTICS:**

Specific Gravity @ 15°C	0.848
Kinematic Viscosity @ 100°C	6.0cSt
Pour Point °C	-42
Flashpoint °C	200
Colour	Red

**HEALTH AND SAFETY:**

Health and Safety Data Sheet 6213 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils  
Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

