



**MILLERS OILS**

millersoils.co.uk

PRODUCT DATA SHEET

**PREMIUM**



AUTOMOTIVE



DATA SHEET NO: 5386

PRODUCT NAME/VISCOSITIES:  
**MILLERMATIC ATF UN**

DESCRIPTION:

An automatic transmission and power steering fluid.

APPLICATION:

For use in automatic transmission and power steering systems as recommended by the vehicle manufacturer.

USER BENEFITS:

- Will provide a high performance in accordance with vehicle manufacturer requirements.
- Very high resistance to oxidation and degradation in use and so suitable for use where very long service intervals are required.
- Ensures a smooth transmission of power.

PERFORMANCE PROFILE:

Suitable for use where the following specifications are called for by the vehicle manufacturer:-

- General Motors Dexron IID
- Ford M2C 138CJ, M2C 166H
- MB 236.2 (Except for GL76, 30-5 & GL275E gearboxes)
- MB 236.4, 236.6, 236.7

TYPICAL CHARACTERISTICS:

Specific Gravity @ 15°C	0.866
Kinematic Viscosity @ 100°C	7.5cSt
Kinematic Viscosity @ 40°C	38.9cSt
Viscosity Index	164
Pour Point °C	-42
Flashpoint °C	210
Brookfield Viscosity @ -40°C	34,000cP
Colour	Red

HEALTH AND SAFETY:

Health and Safety Data Sheet 5405 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited  
Brighouse  
West Yorkshire  
HD6 3DP

Tel +44 (0)1484 713201  
Fax +44 (0)1484 721263  
Email [enquiries@millersoils.co.uk](mailto:enquiries@millersoils.co.uk)  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

