



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



DATA SHEET NO: 5997

PRODUCT NAME/VISCOSITIES:

XF LONGLIFE 3 5w30

DESCRIPTION:

A high performance full synthetic petrol and diesel engine oil suitable for the latest technology petrol and diesel engines.

APPLICATION:

Suitable for use in petrol and diesel engines meeting Euro IV emissions standards, with or without diesel particulate filters.

Particularly recommended by Daimler Chrysler and BMW for use with variable service intervals and other vehicles that require a fuel-efficient lubricant.

USER BENEFITS:

- The high quality of this full synthetic oil means that fuel economy is maximised at the same time as engine wear is being minimised.
- Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection.

PERFORMANCE PROFILE:

- API SM, CF
- ACEA A3, B4, C3
- BMW Longlife 04
- Mercedes-Benz 229.51
- GM/Vauxhall LL-A-025/LL-B-025

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w30
Specific Gravity @ 15°C	0.853
Kinematic Viscosity @ 100°C	11.3cSt
Kinematic Viscosity @ 40°C	69.0
Viscosity Index	158
Pour point C	-40
Flashpoint C	210
Cold Crank Viscosity @ -30°C	5,546cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 5997 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

