



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



DATA SHEET NO: 5659

PRODUCT NAME/VISCOSITIES:

XFE - PD

DESCRIPTION:

High quality semi synthetic diesel engine oil of SAE 5w40 viscosity.

APPLICATION:

Suitable for small diesel engines fitted to cars and light vans especially the VW 'Pumpe Düse' engine fitted to many Volkswagen/Audi Group and some Ford vehicles.

USER BENEFITS:

- Minimises warm up time and provides quick full lubrication under cold and stop/start operating conditions.
- Viscosity maintained over wide operating temperature range.
- Suitable for mixed fleet use.
- Maximises fuel economy.
- Do not use in diesel vehicles fitted with particulate filters.

PERFORMANCE PROFILE:

- API CF
- ACEA B3
- VW 505.00, 505.01
- Ford M2C 917A

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w40
Specific Gravity @ 15°C	0.858
Kinematic Viscosity @ 100°C	13.9cSt
Kinematic Viscosity @ 40°C	88cSt
Viscosity Index	161
Pour Point °C	-42
Flashpoint °C	220
Cold Crank Viscosity @ -30°C	6,000cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 5659 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

Millers Oils Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

