



millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



DATA SHEET NO: 5454

PRODUCT NAME/VISCOSITIES:

XFS 5w50

DESCRIPTION:

Full synthetic high performance engine oil formulated to meet the requirements of engines operating under severe conditions.

APPLICATION:

For use in current and late model cars where this type of advanced engine oil is called for by the manufacturer, especially modern high performance vehicles.

USER BENEFITS:

- Full protection is provided even under extreme operating conditions including long service intervals.
- Its use is essential in modern cars to enable fuel economy to be maximised.
- This engine oil will ensure that full lubrication is achieved both at low and high operating temperatures.
- Full synthetic properties will provide maximum protection against wear and will help reduce oil consumption.

PERFORMANCE PROFILE:

- API SL, CF
- ACEA A3, B3
- Mercedes-Benz 229.1
- VW 500.00, 501.01, 502.00, 505.00
- Original Ford Cosworth requirement.

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade		5w50
Specific Gravity @ 15°C	0.855	
Kinematic Viscosity @ 100°C		17.0cSt
Kinematic Viscosity @ 40°C	133cSt	
Viscosity Index	140	
Pour Point °C		-35
Flashpoint °C		230
Cold Crank Viscosity @ -30°C		6,360cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 5454 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

