



millersoils.co.uk

PRODUCT DATA SHEET
PREMIUM



DATA SHEET NO: 5223

PRODUCT NAME/VISCOSITIES:

XSS 10w40

DESCRIPTION:

Semi synthetic high performance engine oil with higher than average synthetic content, formulated to meet the demanding requirements of today's engines.

APPLICATION:

Recommended for use in modern petrol and diesel engined vehicles where this type of oil is specified by the manufacturer.

USER BENEFITS:

- Provides easy starting and quick circulation of the oil even under very cold conditions.
- Helps to maximise fuel economy and minimise emissions.
- Protects against wear under arduous operating conditions and allows the use of the modern longer oil change service intervals.

PERFORMANCE PROFILE:

- API SL, CF
- ACEA A3/B3
- Mercedes-Benz 229.1
- VW 500.00/502.00/505.00
- PSA B71 2294/2295
- Also meets manual transmission specification MTF-94

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade		10w40
Specific Gravity @ 15°C	0.874	
Kinematic Viscosity @ 100°C		14.2cSt
Kinematic Viscosity @ 40°C	94cSt	
Viscosity Index	156	
Pour Point °C		-36
Flashpoint °C		220
Cold Crank Viscosity @ -25°C		6,570cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 5223 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

