



millersoils.co.uk

PRODUCT DATA SHEET
PREMIUM



DATA SHEET NO: 5611

PRODUCT NAME/VISCOSITIES:

XSS 5w30

DESCRIPTION:

Semi synthetic high performance engine oil with higher than average synthetic content, formulated to meet the demanding requirements of today's engines.

APPLICATION:

Recommended for use in those modern vehicles where this type of oil is specified by the manufacturer.

XSS 5w30 is especially recommended for use in certain Ford, Volvo, Land Rover, Jaguar and other models including diesel engined ones, as well as many modern Japanese vehicles requiring this particular grade.

USER BENEFITS:

- Provides easy starting and quick circulation of the oil even under very cold conditions.
- Helps to maximise fuel economy and minimise emissions.
- Protects against wear under arduous operating conditions.
- Suitable for use in modern vehicles requiring longer oil change service intervals.

PERFORMANCE PROFILE:

- ACEA A1/B1, A5
- Ford M2C913 B

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	5w30
Specific Gravity @ 15°C	0.862
Kinematic Viscosity @ 100°C	9.9cSt
Kinematic Viscosity @ 40°C	56.2cSt
Viscosity Index	165
Pour Point °C	-36
Flashpoint °C	220
Cold Crank Viscosity @ -30°C	6,500cP

HEALTH AND SAFETY:

Millers Oils
Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk





MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



Health and Safety Data Sheet 5611 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
Limited
Brighouse
West Yorkshire
HD6 3DP

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

