



MILLERS OILS

millersoils.co.uk

PRODUCT DATA SHEET

PREMIUM



AUTOMOTIVE



DATA SHEET NO: 5862

PRODUCT NAME/VISCOSITIES:

XF LONGLIFE 5w30

DESCRIPTION:

A high performance full synthetic petrol and diesel engine oil suitable for the latest technology petrol and diesel engines.

APPLICATION:

Suitable for use in most petrol and diesel engines meeting Euro IV emissions standards, with or without diesel particulate filters.

Particularly recommended by VAG for use with variable service intervals (WIV) and other vehicles that require a fuel-efficient lubricant.

USER BENEFITS:

- The high quality of this oil means that fuel economy is maximised at the same time as engine wear is being minimised.
- Oil viscosity or thickness is maintained even under the most severe of operating conditions thereby ensuring maximum engine protection.

PERFORMANCE PROFILE:

- ACEA A3/B4
- VW 504.00, 507.00
- Mercedes-Benz 229.51

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade		5w30
Specific Gravity @ 15°C	0.849	
Kinematic Viscosity @ 100°C		11.9cSt
Kinematic Viscosity @ 40°C	71.0cSt	
Viscosity Index	158	
Pour Point °C		-40
Flashpoint °C		210
Cold Crank Viscosity @ -30°C		6,140cP

HEALTH AND SAFETY:

Health and Safety Data Sheet 5862 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

Millers Oils
Limited
Brighouse
West Yorkshire
WF6 2BB

Tel +44 (0)1484 713201
Fax +44 (0)1484 721263
Email enquiries@millersoils.co.uk
www.millersoils.co.uk

